

ATTRIBUTE AUTHENTICATION (ANONYMOUS AUTHENTICATION)

Martin Primas

13.4.2013

Example - access system into block of flats

2

I want to go home.



~~(Who are you?)~~
Do you live here?

Privacy and digital identity

3

- Identification is not necessary for many services
 - ▣ Access systems into block of flats
 - ▣ Library
 - ▣ Proving legal drinking age
 - ▣ Internet magazines with advance payment
- Protection of privacy
 - ▣ Anonymity - Identity should be published during the verification only with reason.
 - ▣ Untraceability - Service provider should not be able to trace issued token and verification sessions.
 - ▣ Unlinkability - Verification sessions of a single user should not be linkable.

Attribute authentication

4

- Attribute authentication provide more privacy for users (described above).
 - ▣ Only necessary information about user is released in verification protocol.
- There is more possibilities for revocation (hard task to provide it):
 - ▣ Revocation of Unlinkability
 - ▣ Revocation of Credential (Untraceability / Access right)
 - ▣ Revocation of Anonymity


Known systems

5

- Known systems
 - ▣ U-Prove from Microsoft (missing Unlinkability)
 - ▣ Idemix (Identity Mixer) from IBM
- Missing in both systems
 - ▣ Revocation of Credential
 - ▣ Revocation of Anonymity (could be added)
- New system was described by VUT in Brno
 - ▣ OKsystem, where I worked, cooperated on review of the system and have started with developing on smart card.
 - ▣ **The system is described below.**

Communication scheme

6



Entities

7

- Issuer
 - ▣ issues personal attributes to users
 - ▣ cooperates during the revocation of anonymity
- Revocation Referee (added entity)
 - ▣ works as a privacy guarantee
 - ▣ cooperates during the revocation of anonymity
 - ▣ cooperates with the Issuer during the attribute issuance
 - ▣ does not know private user information
- User
 - ▣ can anonymously prove the attribute ownership
- Verifier
 - ▣ verifies User's attribute ownership
 - ▣ can ask Revocation Referee for revocation

Used Cryptographic Primitives

8

- Okamoto-Uchiyama trapdoor one-way function
 - ▣ $n = r^2s$; r, s are large primes
 - ▣ g from Z_n ; $g \bmod r^2$ is a primitive element of $Z_{r^2}^*$
 - ▣ Then $\mathbf{c} = \mathbf{g}^x \bmod \mathbf{n}$ is a trapdoor one-way function with r as a trapdoor:
$$x = \frac{((c^{r-1} \bmod r^2) - 1)/r}{((g^{r-1} \bmod r^2) - 1)/r} \bmod r$$
- Discrete logarithm commitments
 - ▣ $p : q | p-1$ be a large prime and
 - ▣ g a generator of order q in Z_p .
 - ▣ Then $\mathbf{c} = \mathbf{g}^w \bmod \mathbf{p}$ is a simple commitment scheme with commitment w
- Proofs of knowledge of discrete logarithm
 - ▣ Notation: $\mathbf{PK}\{\mathbf{a}: \mathbf{c} = \mathbf{g}^{\mathbf{a}}\}$

IssueAtt Protocol

9

RR

User

Issuer

$$w_1, w_2 \in_R \{0, 1\}^l$$

$$C_I = \text{commit}(w_1, w_2) = h_1^{w_1} h_2^{w_2} \bmod p$$

$$\frac{PK\{w_1, w_2 : C_I = h_1^{w_1} h_2^{w_2}\}, \text{Sig}_U(C_I)}{\text{Store } (C_I, \text{Sig}_U(C_I))}$$

$$\xleftarrow{\text{Sig}_I(C_I)}$$

$$A'_{seed} = g_1^{w_1} g_2^{w_2} \bmod n$$

$$\frac{A'_{seed}, C_I, \text{Sig}_I(C_I), PK\{(w_1, w_2) : C_I = h_1^{w_1} h_2^{w_2} \wedge A'_{seed} = g_1^{w_1} g_2^{w_2}\}}{\xleftarrow{w_{RR} : A_{seed} = g_1^{w_1} g_2^{w_2} g_3^{w_{RR}} \bmod n} \rightarrow}$$

User master key for A_{seed} : $K_U = (w_1, w_2, w_{RR})$

ProveAtt Protocol in Camenisch-Stadler Notation

10

RR

User

Verifier

$$A_{seed} = g_1^{w_1} g_2^{w_2} g_3^{w_{RR}} \bmod n$$

$$K_S \in_R \{0, 1\}^l$$

$$A = A_{seed}^{K_S} \bmod n$$

$$C_1 = g_3^{K_S w_{RR}} \bmod n$$

$$C_2 = g_3^{K_S} \bmod n$$

$$PK\{(K_S, K_S w_1, K_S w_2, K_S w_{RR}) : A = g_1^{K_S w_1} g_2^{K_S w_2} g_3^{K_S w_{RR}} \wedge A = A_{seed}^{K_S} \wedge C_1 = g_3^{K_S w_{RR}} \wedge C_2 = g_3^{K_S}\}$$

- RR knows the trapdoor function, RR is able to
 - ▣ derive K_S from C_2 and then
 - ▣ derive w_{RR} from C_1 and from K_S

Revoke Protocol

11

- Unlinkability revocation
 - ▣ RR can calculate w_{RR} and w'_{RR} from two transcripts of the ProveAtt protocol
 - ▣ If $w_{RR} = w'_{RR}$, then the session has been carried out by the same User.
- Credential revocation
 - ▣ RR can publish revocation information $rev = w_{RR}$ on a public blacklist
 - ▣ Each Verifier is able to check if the User is blacklisted or not by checking $C_1 = C_2^{rev} \bmod n$.
- Anonymity revocation
 - ▣ RR can reveal w_{RR} and corresponding C_i since both values are linked by the IssueAtt protocol
 - ▣ C_i is then forwarded to Issuer who can de-anonymize the User

Thank you for attention.

Any questions?